LA SEMAFORICA

L2

Flashing Device

GENERAL CHARACTERISTICS

- Two-channels flashing device
- Flashing frequency adjustable from frontal trimmer
- Installation of the module through DIN guides and screws
- Operating temperature from -40°C to +60°C
- Power supply 230 V
- Maximum power 700 W for each channel
- 4M box per DIN guide (70x90x60 mm)
- To make the installation of the module L2M easier, it is provided with a PVC housing with Protection Degree IP55 and dimensions 195 mm (H) x 150 mm (L) x 80 mm (P).
- CE conformity

CONFIGURATIONS

- L2M Only flashing module
- L2C Module complete with housingIP55

Also available: Module with Power supply 12 Vdc max 30 W per output for applications with solar panels

APPLICATIONS

- Flashing signalling
- Flashing warning signals
- Signalling of danger

LA SEMAFORICA - L2 REV. February 2026 ENG
In order to offer the best possible service, La Semaforica reserves the right to modify at any moment and without any warning the features of the products described in this document. This document has the only purpose of illustrating the products. If you need detailed technical data, please do not hesitate to contact us.

LA SEMAFORICA
Via Ponticello, 17 - 35129 Padova (PD) - ITALY
+39 049 773055 +39 049 8074002
www.lasemaforica.com info@lasemaforica.com